

CHRISTO-LUBE® 470

Formerly called AbsoLube 470

CHRISTO-LUBE® 470 is synthetic grease made from perfluoropolyether fluid thickened with an organic thickener system. This grease is inert to aggressive chemicals, fuels, water, and oxygen. It has excellent compatibility with almost all plastics and elastomers. This material has no flash point. PFPE fluids have extremely low surface tension that allows them to work in situations where other lubricants fail due to lubricant starvation.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
Type		PFPE
Temperature Service Range (°C)		-40 to 130
Flash Point (°C) (ASTM D92)		None
GREASE CHARACTERISTICS		TYPICAL VALUE *
Thickener		Organic
Color		White
Appearance		Smooth
NLGI Grade		2
Penetration (ASTM D217)	Unworked	265-295
	Worked	60X 265-295
Dropping Point (°C) (ASTM D2265)		137
Oil Separation (ASTM D6184)	24h at 100°C	4.90%
Evaporation (CTM-1)	24h at 100°C	0.02%
Copper Corrosion (ASTM D4048)	24h at 100°C	1b
Specific Gravity (CTM-2)	25°C	1.78

*The values stated in this Product Data Sheet are Typical Values and **must not** be used as QC Specifications for this product. Please contact the Global Technical Services department for QC specifications for this product.

Engineered Custom Lubricants

IATF 16949 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: eclusa_customer@quakerhoughton.com • www.ecllube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications.