



A QUAKER HOUGHTON COMPANY

Innovation and Experience at Work

# Product Data Sheet

## Friction Fighter®

Friction Fighter® PTFE Powder is a soft powdered polytetrafluoroethylene dry lubricant. The product is insoluble in all solvents and will not lump or agglomerate. It's very low coefficient of friction and self-lubricating characteristics make this an excellent additive to a variety of media including general-purpose engineered plastics, waxes, paints, coatings, grease, and oil.

CHARACTERISTICS	TYPICAL VALUE *
Temperature Service Range (°C)	-60 to 200
Color	White
Appearance	Free-flowing Powder
Specific Gravity	2.15 – 2.20
Melting Point	321°C
Average Particle Size	10 microns
Usable Temperature Range (°C)	-240 to +305

\*The values stated in this Product Data Sheet are Typical Values and **must not** be used as QC Specifications for this product. Please contact the Global Technical Services department for QC specifications for this product.

### Engineered Custom Lubricants

IATF 16949 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: [eclusa\\_customer@quakerhoughton.com](mailto:eclusa_customer@quakerhoughton.com) • [www.ecllube.com](http://www.ecllube.com)

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications.