

## CHRISTO-LUBE® MCG 110

CHRISTO-LUBE® MCG 110 is a fully fluorinated, medium viscosity PFPE grease thickened with PTFE. This grease operates under extreme temperature conditions, has outstanding stability with oxygen and excellent compatibility with metals, plastics and elastomers. This soft consistency fluorinated lubricant is especially useful where non-reactivity with harsh chemicals, fuels and solvents is an important factor.



This product is registered H1 by the NSF (135017)

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
Type		PFPE
Temperature Service Range (°C)		-60 to 260
Flash Point (°C) (ASTM D92)		None
GREASE CHARACTERISTICS		
Thickener		PTFE
Color		White
Appearance		Smooth
NLGI Grade		0
Penetration (ASTM D217 / DIN 51804-T1)	Unworked	355-385
	Worked	60X 355-385
Oil Separation (ASTM D6184)	24h at 149°C	15% max.
Evaporation (CTM-1)	24h at 149°C	1% max.
Specific Gravity (CTM-2)	25°C	1.99

\*The values stated in this Product Data Sheet are Typical Values and **must not** be used as QC Specifications for this product. Please contact the Global Technical Services department for QC specifications for this product.