

TriboGel 968VL BLUE

TriboGel 968VL BLUE is a synthetic hydrocarbon polytetrafluoroethylene thickened light dampening grease. This grease is fortified with a corrosion inhibitor and an extreme pressure additive.

| BASE OIL CHARACTERISTICS | | TYPICAL VALUE * | |
|--|--|-----------------------|------------|
| Type | | Synthetic Hydrocarbon | |
| Temperature Service Range (°C) | | -45 to 120 | |
| GREASE CHARACTERISTICS | | TYPICAL VALUE * | |
| Thickener | | PTFE | |
| Color | | Blue | |
| Appearance | | Smooth | |
| NLGI Grade | | 2 | |
| Penetration (ASTM D217 / DIN 51804-T1) | Unworked | 265-295 | |
| | Worked | 60X 265-295 | |
| Oil Separation (ASTM D6184) | 24h at 100°C | 2% max. | |
| Evaporation (CTM-1) | 24h at 100°C | 1% max. | |
| Four Ball Wear (ASTM D2266 / DIN 51350-T5) | 60 min 1200 RPM 75°C 40kg _f | 0.73mm | |
| Low Temperature Torque (ASTM D1478) | -40°C | Start | 1,892 g-cm |
| | | Run 60 min | 780 g-cm |

*The values stated in this Product Data Sheet are Typical Values and **must not** be used as QC Specifications for this product. Please contact the Global Technical Services department for QC specifications for this product.