

## ViscoTech 3125

ViscoTech 3125 is a lithium combination-type grease modified with PTFE. It contains non-corrosive and extreme pressure additives and is water resistant. The light viscosity oil makes this grease ideal for many types of high-speed applications where fluid-friction must be kept to a minimum.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
<b>Type</b>		Mineral Oil
<b>Temperature Service Range (°C)</b>		-30 to 100
GREASE CHARACTERISTICS		TYPICAL VALUE *
<b>Thickener</b>		Lithium Combination
<b>Color</b>		Tan
<b>Appearance</b>		Smooth
<b>NLGI Grade</b>		2
<b>Penetration</b> (ASTM D217 / DIN 51804-T1)	Unworked	265-295
	Worked	60X 265-295
<b>Dropping Point (°C)</b> (ASTM D2265 / DIN ISO 2176)		260 min.
<b>Oil Separation</b> (ASTM D6184)		24h at 100°C 5% max.
<b>Evaporation</b> (CTM-1)		24h at 100°C 5% max.
<b>Specific Gravity</b> (CTM-2)		25°C 1.08

\*The values stated in this Product Data Sheet are Typical Values and **must not** be used as QC Specifications for this product. Please contact the Global Technical Services department for QC specifications for this product.