

## ViscoTech TEK662

ViscoTech TEK662 was specifically developed for use in heavy-duty applications. This product has proven to be extremely efficient in applications for Heavy Duty Truck Brake Systems. It provides excellent water washout protection and long wheel bearing life.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *	
<b>Type</b>		Mineral Oil	
<b>Temperature Service Range (°C)</b>		-15 to 100	
GREASE CHARACTERISTICS		TYPICAL VALUE *	
<b>Thickener</b>		Overbased Calcium Sulfonate	
<b>Color</b>		Black	
<b>Appearance</b>		Smooth	
<b>NLGI Grade</b>		2	
<b>Penetration (ASTM D217)</b>	Unworked	265-295	
	Worked	60X	265-295
		10,000X	269
	100,000X	272	
<b>Dropping Point (°C) (ASTM D2265)</b>		260 min.	
<b>Oil Separation (ASTM D6184)</b>	24 h at 100°C	3% max.	
<b>Oil Separation (ASTM D1742)</b>	24h at 25°C and 1.72 kPa	0.17%	
<b>Evaporation (CTM-1)</b>	24 h at 100°C	2% max.	
<b>Water Washout (ASTM D1264)</b>	60 min at 79°C	2.75%	
<b>Rust Test Rating (ASTM D1743)</b>		1,1,1	
<b>Roll Stability (ASTM D1831) Pen</b>		19	
<b>Four Ball EP (ASTM D2596)</b>	LWI	65 kg	
	Weld Point	500 kg	
<b>Four Ball Wear (ASTM D2266)</b>	60 min 1200 RPM 75°C 40kg <sub>f</sub>	0.39mm	
<b>Specific Gravity (CTM-2)</b>	25°C	0.96	
<b>Oxidation Stability (ASTM D942)</b>	100h at 100°C	0 kPa	
	500h at 100°C	14 kPa	
	1000h at 100°C	62 kPa	

\*The values stated in this Product Data Sheet are Typical Values and **must not** be used as QC Specifications for this product. Please contact the Global Technical Services department for QC specifications for this product.