

CHRISTO-LUBE® 5130

Formerly called AbsoLube 5130

CHRISTO-LUBE® 5130 is PFPE fluid cut with non-combustible fluorinated solvent. When this material is applied, the solvent evaporates and leaves behind a thin film of oil. This lubricant has excellent low temperature properties and is inert to oxygen and other aggressive chemicals. The PFPE fluid has extremely low surface tension and this gives CHRISTO-LUBE® 5130 the ability to work in applications where other lubricants fail due to lubricant starvation. The fully fluorinated chemistry is completely compatible with a vast majority of plastics and elastomers.

CHARACTERISTICS	TYPICAL VALUE *
Temperature Service Range (°C)	-75 to 250
Type	PFPE
Color	Colorless
Flash Point (°C) (ASTM D-92)	None
Specific Gravity at 25°C	1.83

Engineered Custom Lubricants

ISO/TS16949:2009 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: customerservice@ecllube.com • www.ecllube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.