

## CHRISTO-LUBE® B4039

Formerly called AbsoLube B4039

CHRISTO-LUBE® B4039 is high technology perfluoropolyether fluid that possesses excellent thermal stability and resistance to chemicals and oxygen-rich environment. Its very low pour point and excellent oxidative stability allow it to function in a very broad temperature range. Since it is non-reactive with metal, plastic, rubber, and other elastomers, it is useful in a wide variety of applications. PFPE fluids have extremely low surface tension that allows them to work in situations where other lubricants fail due to lubricant starvation.

CHARACTERISTICS		TYPICAL VALUE *
Type		PFPE
Color		Colorless
Temperature Service Range (°C)		-40 – 200
Flash Point (°C) (ASTM D-92)		None
Four Ball Wear (ASTM D2266 / DIN 51350-T5)	60min 1200rpm 40kg <sub>f</sub> 75°C	0.7mm

**Engineered Custom Lubricants**

ISO/TS16949:2009 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: [customerservice@ecllube.com](mailto:customerservice@ecllube.com) • [www.ecllube.com](http://www.ecllube.com)

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.