



*Innovation and Experience at Work*

## CHRISTO-LUBE® MCG 1011K

CHRISTO-LUBE® MCG 1011K is a fully fluorinated oil which operates under extreme temperature conditions, has outstanding stability with oxygen and excellent compatibility with metals, plastics and elastomers. This medium viscosity PFPE oil is especially useful in lubricating plastic and elastomer components commonly found in automotive applications.

CHARACTERISTICS		TYPICAL VALUE *
<b>Type</b>		PFPE
<b>Color</b>		Colorless
<b>Temperature Service Range (°C)</b>		-30 to 200
<b>Flash Point (°C) (ASTM D-92)</b>		None
<b>Evaporation (ASTM-2595)</b>	22h at 121°C	1%
	22h at 204°C	7%
<b>Specific Gravity (CTM-2)</b>		1.94
<b>Four Ball Wear (ASTM D2266 / DIN 51350-T5)</b>		60min 1200rpm 40kg <sub>f</sub> 75°C

**Engineered Custom Lubricants**

ISO/TS16949:2009 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: [customerservice@ecllube.com](mailto:customerservice@ecllube.com) • [www.ecllube.com](http://www.ecllube.com)

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.