



Innovation and Experience at Work

CHRISTO-LUBE® MCG 173

CHRISTO-LUBE® MCG 173 is a fully fluorinated, high viscosity PFPE grease thickened with PTFE. This grease operates under extreme temperature conditions, has outstanding stability with oxygen and excellent compatibility with metals, plastics and elastomers. This medium consistency fluorinated lubricant is especially useful where non-reactivity with harsh chemicals, fuels and solvents is an important factor.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
Type		PFPE
Temperature Service Range (°C)		-45 to 300
Flash Point (°C) (ASTM D92)		None
GREASE CHARACTERISTICS		TYPICAL VALUE *
Thickener		PTFE
Color		White
Appearance		Smooth
NLGI Grade		2
Penetration (ASTM D217)	Unworked	265-295
	Worked	60X 265-295
Oil Separation (ASTM D6184)	24h at 149°C	10% max.
Evaporation (CTM-1)	24h at 149°C	3% max.
Specific Gravity (CTM-2)	25°C	1.99

*The typical values reported on this data sheet should not be used for writing specifications or creating drawings. Please consult ECL for assistance in preparing a specification for this product. Refer to our product Material Safety Data Sheet for detailed safety information.

Engineered Custom Lubricants

ISO/TS16949:2009 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: customerservice@ecllube.com • www.ecllube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.