



Innovation and Experience at Work

RheoGel 1001

RheoGel 1001 is synthetic hydrocarbon grease specially formulated for the lubrication of non-noble metal electrical connectors. This grease contains oxidation inhibitors to promote long life and ultraviolet dye for post application detection. RheoGel 1001 is compatible with most plastics and elastomers and has low volatility.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
Type		Synthetic Hydrocarbon
Temperature Service Range (°C)		-40 to 125
GREASE CHARACTERISTICS		TYPICAL VALUE *
Thickener		Inorganic
Color		Water White to Amber
Appearance		Smooth
NLGI Grade		2
Penetration (ASTM D217 / DIN 51804-T1)	Unworked	250 min.
	Worked	60X 265-295
Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)		260 min.
Oil Separation (ASTM D6184)	24h at 100°C	5% max.
Evaporation (CTM-1)	24h at 100°C	1% max.
Water Washout (ASTM D1264 / DIN 51807-T2)	60 min at 79°C	1%
Copper Corrosion (ASTM D130 / DIN 51811)	24h at 100°C	1b max.
Specific Gravity (CTM-2)	25°C	0.89
Oxidation Stability (ASTM D942 / DIN 51808)	168h at 100°C	17 kPa

Engineered Custom Lubricants

ISO/TS16949:2009 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: customerservice@ecllube.com • www.ecllube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.