



**Innovation and Experience at Work**

## RheoGel 1720

RheoGel 1720 is synthetic hydrocarbon grease prepared from a lithium-based thickening agent and fortified with additives to improve oxidative stability. This grease had been designed for low temperature automotive interior applications.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *	
Type		Synthetic Hydrocarbon	
Temperature Service Range (°C)		-54 to 125	
GREASE CHARACTERISTICS		TYPICAL VALUE *	
Thickener		Lithium	
Color		Off White	
Appearance		Smooth	
NLGI Grade		2	
Penetration (ASTM D217 / DIN 51804-T1)	Unworked	265-295	
	Worked	60X 265-295	
Dropping Point (°C) (ISO 2176)		190 min.	
Oil Separation (ASTM D6184)	24h at 100°C	3.00%	
Evaporation (CTM-1)	24h at 100°C	0.44%	
Copper Corrosion (DIN 51808)	24h at 100°C	1b	
Apparent Viscosity (CTM-3)	-40°C	2,616,000	
Specific Gravity (CTM-2)	25°C	0.82	
Oxidation Stability (ASTM D942)	100h at 99°C	0.2 bar	
Salt Water Resistance (DIN 51807 T1)	3h at 90°C	1	
Low Temperature Torque (ASTM D1478)	-40°C	Start	472 g-cm
		Run 20 min	118 g-cm
Kesternich Flow Pressure (DIN 51805)	20°C	96/96 mbar*	
	-35°C	275/250 mbar*	

\*The typical values reported on this data sheet should not be used for writing specifications or creating drawings. Please consult ECL for assistance in preparing a specification for this product. Refer to our product Material Safety Data Sheet for detailed safety information.

**Engineered Custom Lubricants**      ISO/TS16949:2009 • Registered QMS  
3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: [customerservice@ecllube.com](mailto:customerservice@ecllube.com) • [www.ecllube.com](http://www.ecllube.com)

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.