



**Innovation and Experience at Work**

## RheoGel 4000NO

RheoGel 4000NO is advanced synthetic hydrocarbon grease prepared from lithium-based thickening agent and fortified with additives to improve oxidative stability and promote film formation during transient sub-elastohydrodynamic operating conditions. This grease has been designed for automotive and industrial rolling element bearing applications.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
Type		Synthetic Hydrocarbon
Temperature Service Range (°C)		-40 to 125
GREASE CHARACTERISTICS		TYPICAL VALUE *
Thickener		Lithium
Color		Off-white to Tan
Appearance		Smooth
NLGI Grade		2
Penetration (ASTM D217 / DIN 51804-T1)	Unworked	250 min.
	Worked	60X 265-295
Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)		200 min.
Oil Separation (ASTM D6184)	24h at 100°C	7% max.
Evaporation (CTM-1)	24h at 100°C	1% max.

**Engineered Custom Lubricants**

ISO/TS16949:2009 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: [customerservice@ecllube.com](mailto:customerservice@ecllube.com) • [www.ecllube.com](http://www.ecllube.com)

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.