



Innovation and Experience at Work

RheoGel 914A

RheoGel 914A is synthetic grease. It provides excellent ferrous corrosion protection and is very shear stable.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
Type		Synthetic Hydrocarbon
Temperature Service Range (°C)		-40 to 125
GREASE CHARACTERISTICS		TYPICAL VALUE *
Thickener		Calcium Sulfonate Complex
Color		Tan
Appearance		Smooth
NLGI Grade		1
Penetration (ASTM D217 / DIN 51804-T1)	Unworked	310-320
	Worked	60X 310-320
Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)		>260
Oil Separation (ASTM D6184)	24h at 100°C	2.4%
Evaporation (CTM-1)	24h at 100°C	0.3%
Apparent Viscosity (Brookfield Viscometer T-C spindle, 1 rpm)	-40°C, T-C Spindle, 1 rpm	3,800,000 cP
	25°C, CP52 Spindle, 10 rpm	28671 cP

Engineered Custom Lubricants

ISO/TS16949:2009 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: customerservice@ecllube.com • www.ecllube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.