



Innovation and Experience at Work

TriboGel 1483

TriboGel 1483 is an automotive and industrial grease intended for wide temperature ranges and demanding applications. This grease has excellent shear stability, load carrying capacity, and ferrous corrosion protection. It also contains molybdenum disulfide for enhanced load carrying and outstanding fretting corrosion protection. TriboGel 1483 is ideal for metal to metal interfaces where noise damping is required.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
Type		Synthetic Hydrocarbon
Temperature Service Range (°C)		-30 to 150
GREASE CHARACTERISTICS		TYPICAL VALUE *
Thickener		Calcium Sulfonate Complex
Color		Black
Appearance		Smooth
NLGI Grade		1-1.5
Penetration (ASTM D217 / DIN 51804-T1)	Unworked	300-330
	Worked	60X 300-330
Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)		260 min.
Oil Separation (ASTM D6184)	24h at 100°C	6% max.
Evaporation (CTM-1)	24h at 100°C	2% max.
Specific Gravity (CTM-2)	25°C	0.955

Engineered Custom Lubricants ISO/TS16949:2009 • Registered QMS
3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: customerservice@ecllube.com • www.ecllube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.