



Innovation and Experience at Work

TriboGel PA6110LCS

TriboGel PA6110LCS is synthetic PAO based grease with outstanding performance over high and low temperature extremes. This product has a service temperature of -40 to 130°C, and is capable of handling intermittent spikes in temperature to 150°C. It has excellent chemical stability and works well with most materials including plastics and elastomers. It resists oxidation and corrosion of metal surfaces. TriboGel PA6110LCS is designed for noise dampening and motion control applications.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
Type		Synthetic Hydrocarbon
Temperature Service Range (°C)		-40 to 130
GREASE CHARACTERISTICS		TYPICAL VALUE *
Thickener		PTFE
Color		White
Appearance		Smooth
NLGI Grade		0.5
Penetration (ASTM D217 / DIN 51804-T1)	Unworked	330-360
Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)		260 min.
Oil Separation (ASTM D6184)	24h at 100°C	3% max.
Evaporation (CTM-1)	24h at 100°C	1% max.
Four Ball Wear (ASTM D2266 / DIN 51350-T5)	60 min 1200 RPM 75°C 40kgf	0.61mm
	Dynamic Coefficient of Friction (steel on steel)	0.046
Apparent Viscosity (Brookfield Viscometer T-C spindle, 1 rpm)	-40°C	3,680,000 cP

Engineered Custom Lubricants

ISO/TS16949:2009 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: customerservice@ecllube.com • www.ecllube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.