

UltraSil 1132

UltraSil 1132 is a silicone damping grease with a polytetrafluoroethylene thickening agent. This grease is useful for plastic on plastic or plastic on metal applications and was formulated for use in window regulators. It provides effective damping at high and low temperatures and has very low oil separation properties.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *	
Type		Silicone	
Temperature Service Range (°C)		-50 to 200	
GREASE CHARACTERISTICS		TYPICAL VALUE *	
Thickener		PTFE	
Color		White	
Appearance		Smooth	
NLGI Grade		2	
Penetration (ASTM D217 / DIN 51804-T1)	Unworked	265-295	
Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)		260 min.	
Oil Separation (ASTM D6184)	24h at 100°C	0%	
Evaporation (CTM-1)	24h at 100°C	0.10%	
Water Washout (ASTM D1264 / DIN 51807-T2)	60 min at 38°C	0.24%	
	60 min at 80°C	1.5%	
Apparent Viscosity (Brookfield Viscometer, 1 rpm)	-40°C, T-C Spindle	2,360,000 cP	
	25°C, T-A Spindle	1,169,600 cP	
Specific Gravity (CTM-2)	25°C	1.20	
Low Temperature Torque (ASTM D1478)	-40°C	Start	442 g·cm
		Run 10 min	265 g·cm
		Run 60 min	177 g·cm

*The values stated in this Product Data Sheet are Typical Values and **must not** be used as QC Specifications for this product. Please contact the Global Technical Services department for QC specifications for this product.