



**Innovation and Experience at Work**

## UltraSil 500

UltraSil 500 is a high performance grease based on a silicone oil. It can be used for lubrication of plastic/metal (i.e. aluminium) as well as plastic/plastic applications. UltraSil 500 was developed to meet fill-for-life requirements, especially at low temperature conditions in the OEM automotive sector (sunroof, window regulators, cables, actuators and others). It provides excellent water washout resistance as well as very good noise dampening properties. Special features of this grease: Excellent water resistant. Clear color (best choice for the use of tracks and other visual parts). Compatible with almost all types of plastic and elastomers. Very good resistant against dust.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
<b>Type</b>		Silicone
<b>Temperature Service Range (°C)</b>		-50 to 200
GREASE CHARACTERISTICS		TYPICAL VALUE *
<b>Thickener</b>		Silica
<b>Color</b>		Clear *
<b>Appearance</b>		Smooth
<b>NLGI Grade</b>		1.5
<b>Penetration (ASTM D217 / DIN 51804-T1)</b>	Unworked	285-315
	Worked	60X 285-315
<b>Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)</b>		260 min.
<b>Oil Separation (ASTM D6184)</b>	24h at 100°C	2% max.
<b>Evaporation (CTM-1)</b>	24h at 100°C	0.5% max.
<b>Water Washout (ASTM D1264 / DIN 51807-T2)</b>	60 min at 41°C	0.70%
<b>Water Washout (ASTM D1264 / DIN 51807-T2)</b>	60 min at 79°C	1.31%
<b>Specific Gravity (CTM-2)</b>	25°C	0.98
<b>Four Ball Wear (ASTM D2266 / DIN 51350-T5)</b>	15 min, 1200 RPM, 25psi, 75°C, 40kg	1.27mm
	Dynamic Coefficient of Friction (steel on steel)	0.300
<b>Apparent Viscosity</b> (Brookfield Viscometer T-C spindle 1 rpm)	-40°C	1,500,000 cP

\* This product may turn yellow in color over time in the application, but the color change will have no impact on performance.

**Engineered Custom Lubricants**

ISO/TS16949:2009 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: customerservice@ecllube.com • [www.ecllube.com](http://www.ecllube.com)

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.