



Innovation and Experience at Work

UltraSil 917

UltraSil 917 is a silicone-based grease thickened with PTFE. It is a food grade grease that is compatible with EPDM rubber and other non-silicone elastomers. It is an excellent lubricant for o-rings and seals used in beverage and food processing and dispensing equipment.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
Type		Silicone
Temperature Service Range (°C)		-50 to 150
GREASE CHARACTERISTICS		TYPICAL VALUE *
Thickener		PTFE
Color		White
Appearance		Smooth
NLGI Grade		3
Penetration (ASTM D217)	Unworked	220 min.
	Worked	220-250
Dropping Point (°C) (ASTM D2265)		260 min.
Oil Separation (ASTM D6184)		24h at 100°C
Evaporation (CTM-1)		24h at 100°C
Four Ball Wear (ASTM D2266 / DIN 51350-T5)		60 min 1200 RPM 75°C 40kg _r
		Dynamic Coefficient of Friction (steel on steel)

Engineered Custom Lubricants

ISO/TS16949:2009 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: customerservice@ecllube.com • www.ecllube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.