



## ViscoTech 0025

ViscoTech 0025 is our original formulation and is still one of our most popular materials. This versatile non-melting grease is used in a variety of applications from sports equipment to automotive OEM products. The wide operating temperature range gives excellent results when used on gears and hardware mechanisms having a low temperature torque requirement.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
<b>Type</b>		Mineral Oil
<b>Temperature Service Range (°C)</b>		-35°C to 150°C
GREASE CHARACTERISTICS		TYPICAL VALUE *
<b>Thickener</b>		Bentone
<b>Color</b>		Amber
<b>Appearance</b>		Smooth
<b>NLGI Grade</b>		1
<b>Penetration (ASTM D217)</b>	Unworked	300-330
	Worked	60X 300-330
<b>Dropping Point (°C) (ASTM D2265)</b>		260 min.
<b>Oil Separation (ASTM D6184)</b>		24h at 100°C 5% max.
<b>Evaporation (CTM-1)</b>		24 h at 100°C 3% max.
<b>Specific Gravity (CTM-2)</b>		25°C 0.935
<b>Low Temperature Torque (ASTM D1478)</b>	-40°C	Start 0.3 Nm
		Run 60 min 0.2 Nm

\*The typical values reported on this data sheet should not be used for writing specifications or creating drawings. Please consult ECL for assistance in preparing a specification for this product. Refer to our product Material Safety Data Sheet for detailed safety information.