



Innovation and Experience at Work

ViscoTech 1800

ViscoTech 1800 is mineral oil based grease fortified with additives to promote extreme pressure, anti-wear, oxidation resistance, and corrosion protection.

BASE OIL CHARACTERISTICS		TYPICAL VALUE *
Type		Mineral Oil
Temperature Service Range (°C)		-30 - 150
GREASE CHARACTERISTICS		TYPICAL VALUE *
Thickener		Inorganic
Color		Red
Appearance		Smooth
NLGI Grade		1 ½
Penetration (ASTM D217 / DIN 51804-T1)	Worked 60X	295
Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)		>280
Bearing Corrosion (ASTM D1743)	48h at 52°C	Pass
Four Weld Load Wear Index (ASTM D2596)		45

Engineered Custom Lubricants ISO/TS16949:2009 • Registered QMS
3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: customerservice@ecllube.com • www.ecllube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.