



*Innovation and Experience at Work*

## ViscoTech 2118

ViscoTech 2118 is made with a light mineral oil and a Bentone clay thickening system. It also contains PTFE for good low friction behavior. A good all-purpose grease with decent water resistance and low bleed characteristics.

GREASE CHARACTERISTICS		TYPICAL VALUE *
<b>Temperature Service Range (°C)</b>		-30 to 100
<b>Thickener</b>		Bentone
<b>Color</b>		Brown
<b>Appearance</b>		Smooth
<b>NLGI Grade</b>		1.5
<b>Penetration (ASTM D217 / DIN 51804-T1)</b>	Unworked	275-310
	Worked	60X 275-310
<b>Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)</b>		260 min.
<b>Oil Separation (ASTM D6184)</b>	24h at 100°C	5% max.
<b>Evaporation (CTM-1)</b>	24h at 100°C	3% max.
<b>Water Washout (ASTM D1264 / DIN 51807-T2)</b>	60 min at 38 °C	4.6%

**Engineered Custom Lubricants**      ISO/TS16949:2009 • Registered QMS  
3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: [customerservice@ecllube.com](mailto:customerservice@ecllube.com) • [www.ecllube.com](http://www.ecllube.com)

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.