



Innovation and Experience at Work

ViscoTech TEK553

ViscoTech TEK553 is a petroleum based aluminum complex thickened grease with outstanding high temperature and water spray resistant properties containing solid lubricant additives including zinc oxide.

BASE OIL CHARACTERISTICS			TYPICAL VALUE *
Type			Mineral Oil
Temperature Service Range (°C)			-30 to 100
GREASE CHARACTERISTICS			TYPICAL VALUE *
Thickener			Aluminum Complex
Color			White
Appearance			Smooth
NLGI Grade			2
Penetration (ASTM D217 / DIN 51804-T1)	Worked	60X	265-295
Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)			232°C min

Engineered Custom Lubricants ISO/TS16949:2009 • Registered QMS
3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: customerservice@eclube.com • www.eclube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications. ECLI Products, LLC, owns and does business as Engineered Custom Lubricants and Lubrication Technology.