

## EvoLube CVJ-R

This evolutionary new generation polyurea-thickened grease has outstanding long-life properties. Polyurea thickeners act to inhibit oxidation thereby adding to the long life effectiveness of this grease. EvoLube CVJ-R is a shear stable, multi-purpose, water resistant grease that has excellent low temperature properties and is compatible with most plastics and seals. It is designed particularly for CV Joints in racing applications and is suitable for operating temperatures from -40°C to 150°C.

BASE OIL CHARACTERISTICS			TYPICAL VALUE *
<b>Type</b>			Mineral Oil
<b>Temperature Service Range (°C)</b>			-40 to 150
GREASE CHARACTERISTICS			TYPICAL VALUE *
<b>Thickener</b>			Polyurea
<b>Color</b>			Green
<b>Appearance</b>			Smooth
<b>NLGI Grade</b>			1.5
<b>Penetration</b> (ASTM D217 / DIN 51804-T1)	Worked	60X	290-320
		100,000X	336
<b>Dropping Point (°C)</b> (ASTM D2265)			260 min.
<b>Oil Separation</b> (ASTM D1742)			24h at 25°C and 1.72 kPa
<b>Water Washout</b> (ASTM D1264)			60 min at 80°C
<b>Four Ball Wear</b> (ASTM D2266)			60 min 1200 RPM 75°C 40kg <sub>f</sub>
<b>Specific Gravity</b> (CTM-2)			25°C
<b>Four Ball EP</b> (ASTM D2596)	Load Wear index		86
	Weld Point		500 kg

\*The values stated in this Product Data Sheet are Typical Values and **must not** be used as QC Specifications for this product. Please contact the Global Technical Services department for QC specifications for this product.