



A QUAKER HOUGHTON COMPANY

Innovation and Experience at Work

Product Data Sheet

TriboGel 1363

TriboGel 1363 is a synthetic NLGI #2 grade lithium 12-hydroxystearate thickened grease. It is polymer fortified to improve adhesion and dampening. It is suitable for a wide range of applications.

| BASE OIL CHARACTERISTICS | | TYPICAL VALUE * |
|----------------------------------|--------------|-----------------------|
| Type | | Synthetic hydrocarbon |
| Temperature Service Range (°C) | | -50 to 125 |
| GREASE CHARACTERISTICS | | TYPICAL VALUE * |
| Thickener | | Lithium |
| Color | | Green |
| Appearance | | Smooth |
| NLGI Grade | | 2 |
| Penetration (ASTM D217) | Unworked | 265-295 |
| | Worked | 60X 265-295 |
| Dropping Point (°C) (ASTM D2265) | | 202 |
| Oil Separation (ASTM D6184) | 24h at 100°C | 4.4% |
| Evaporation (CTM-1) | 24h at 100°C | 0.13% |
| Specific Gravity (CTM-2) | 25°C | 0.85 |

*The values stated in this Product Data Sheet are Typical Values and **must not** be used as QC Specifications for this product. Please contact the Global Technical Services department for QC specifications for this product.

Engineered Custom Lubricants

IATF 16949 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: eclusa_customer@quakerhoughton.com • www.eclube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications.