



A QUAKER HOUGHTON COMPANY

Innovation and Experience at Work

Product Data Sheet

ViscoTech 1800

ViscoTech 1800 is a mineral oil based grease fortified with additives to promote extreme pressure, anti-wear, oxidation resistance, and corrosion protection.

BASE OIL CHARACTERISTICS			TYPICAL VALUE *
Type			Mineral Oil
Temperature Service Range (°C)			-30 to 150
GREASE CHARACTERISTICS			TYPICAL VALUE *
Thickener			Inorganic
Color			Red
Appearance			Smooth
NLGI Grade			1.5
Penetration (ASTM D217 / DIN 51804-T1)	Worked	60X	295
Dropping Point (°C) (ASTM D2265 / DIN ISO 2176)			280 min.
Bearing Corrosion (ASTM D1743)	48h at 52°C		Pass
Four Ball EP Weld Load Wear Index (ASTM D2596)			45

*The values stated in this Product Data Sheet are Typical Values and **must not** be used as QC Specifications for this product. Please contact the Global Technical Services department for QC specifications for this product.

Engineered Custom Lubricants

IATF 16949 • Registered QMS

3851 Exchange Ave. • Aurora, IL 60504 • T: 630.449.5000 • F: 630.585.0050 • E: eclusa_customer@quakerhoughton.com • www.eclube.com

DISCLAIMER: Since we cannot anticipate or control the many different conditions under which this information and our product may be used, we cannot guarantee the applicability of this information or the suitability of our product in any individual situation. For the same reason, the product discussed is sold without warranty expressed or implied. Please contact Engineered Custom Lubricants for assistance and recommendations prior to writing or releasing any engineering specifications.